

- Step 1** Lay out all the parts and identify each one by comparing them to the drawings.
- Step 2** Bolt the 2 outside front legs to the seat support with 3" bolts. Use a large washer under each end of the bolt. Make sure the end of the legs with the greater angle is down. And the point of the angle forward. Then do the same with 2 middle front legs, with the notch to the top & front. (Finger tighten the nuts for now). Now put 4 wood screws in through the front piece of the seat and into the outside front legs. Turn the screws in until the heads are sunk in even with the wood. Tighten up all 4 bolts.
- Step 3** Fasten the 4 back legs to the inside of the seat supports on both as shown with the square end down and the top end with the longest angle turned to the back, use 3" bolts & large washes.
- Step 4** Place the 2 backs with the upper supports on top of the back of the legs. Move the top of the back legs forward or backwards, until the lower back support fits into the notches on the seat supports. Fasten 8 screws through the upper back support, into the back legs, keeping the legs even with the ends of the upper back support. Fasten 8 screws through the lower back support into the seat support.
- Step 5** Fasten the back table support to the front of the 2 middle back legs, with 4 screws, with the top edge of the table support 20" from the floor and the 2 middle screws holes up. Do the same with the front table support, setting it in the notches in the 2 middle front legs. Then set the table assembly on the table supports, with the 2 – 2x2 between the front and back table supports. Fasten 2 screws through the front table support; into the 2x2 then fasten the back of the table with 2 screws in through the back of the table support.
- Step 6** Fasten the 2 arms to the outside of the outside back legs with the 2 – 3-1/2" carriage bolts, using a small washer, inside, under the nut only. Put 2 screws down through the holes in each arm into the top of front legs.

Parts List For Adirondack Settee

1 – Seat Assembly	2 – Back assemblies
2 – Arms	2 – Outside Front Legs
2 – Middle Front Legs	4 – Back Legs
1 – Back Table Support	1 – Table Assembly
8 – 3" Hexhead Bolts	2 – 3-1/2" Carriage Bolts
16 – 1/4" x 1" Washers	2 – 1/4" Washers
10 – 1/4" Nuts	34 – Screws

Tools needed for assembly:

- Phillips head screwdriver or drill.
- Pliers or 1/4" socket set.
- Hammer for tapping bolts and screws.

